

## PRODUCT DESCRIPTION

The **BF PUFF SANDY GLITTER** series consists of films with extremely fine glitter applied to the surface and features a special “puff” effect that activates during thermal transfer, **tripling the thickness up to 500 microns.**

The high quality of the product ensures that the glitter remains permanently on the surface even after countless washes.

This series of heat transfer vinyls is ideal for adding ultra-bright, three-dimensional, and high-impact details on cotton garments, synthetic fabrics, blends, and elastic materials.

## APPLICATION TECHNIQUES

- Knockout (*do not overlap the liner of one color of BF PUFF with another*)
- Layering on other series

## APPLICATION STEPS

- Cut - 60° blade
- Weed excess material
- Turn on your heat press - bring the temperature to the desired level
- Pressure setting - medium
- Place your graphic on the garment
- Make sure the surface is even and there are no obstacles such as zippers, buttons or collars
- Press it - follow application instructions
- Remove the liner - hot

 For optimal results, the BF PUFF series requires the use of **an even pressure.**

**Application on Nylon and stiff fabrics is not recommended, as they do not guarantee an optimal “puff” effect.**

**Due to the different chemical composition of each color, the final effect may slightly vary depending on the fabric used, the pressure, and the temperature of the heatpress.**

## WASH RESISTANCE

First wash after application	wait 12 hours
Wash insideout	
Max wash temperature	40°C - 104°F
Dry clean	✗
Dryer	✗

## SAFETY NOTICE

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information abovementioned in this page. Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications.

## SIZES

H 50 cm

L 25 mt / 10 mt / 5 mt

## TECHNICAL DATA



Film: PU + PET



Thickness: 260μ (±5%)



Liner: adhesive PET



Finish: rough



Textile: cotton, synthetic, mixed and elastic

## PLOTTER SETTING



Cut settings: mirror



Blade: 60°



Minimum cut: 0,5 cm

## APPLICATION



Temperature: 130°C/150°C - 265°F/305°F



Pressure: medium - 3,5 bar - 50 PSI



Time: 8" - 10"



Liner removal: hot

follow us

HEADQUARTERS B-FLEX ITALIA S.r.l. info@b-flexitalia.com | www.b-flexitalia.com

NORTH AMERICA BRANCH B-FLEX AMERICA LLC info@b-flexamerica.com | www.b-flexamerica.com

ASIA-PACIFIC BRANCH B-FLEX PACIFIC PTY LTD info@b-flexpacific.com | www.b-flexpacific.com



## BF PUFF SANDY GLITTER



- "Popping" effect
- Glitter on the surface for a sparkling finishing
- Long-lasting glitter



**BF UD700A**  
PUFF SANDY GLITTER WHITE



**BF UD730A**  
PUFF SANDY GLITTER RED



**BF UD751A**  
PUFF SANDY GLITTER APPLE GREEN



**BF UD710A**  
PUFF SANDY GLITTER BLACK



**BF UD792A**  
PUFF SANDY GLITTER GOLD



**BF UD796A**  
PUFF SANDY GLITTER SILVER

